

GEKO SpA

Via dell'Artigianato n° 22

62020 Sant'Angelo in Pontano (MC) – Italy

Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17

Codice Fiscale e P.IVA 00860500438

SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.

Pec gekospa@pec.it | Web www.geko.net | email info@geko.net



GEKO SOFT ADHESIVE - TECHNICAL DATA SHEET 4129

PLASTIC LINER TRANSPARENT

LINER	White PET 80gsm
CARRIER	Transparent PET
ADHESIVE	Clear modified acrylic emulsion
APPLICATION	Lamination of profiles and gaskets.
FEATURES	Very good adhesion; good resistance to temperature, UV and ageing

TECHNICAL DATA

ENLONGATION AT BREAK	110 %
TENSILE STRANGHT	29 N/cm
PEEL 180°	7 N/cm
STATIC SHEAR	>20 h
ROLLING BALL TACK	7 cm
THICKNESS	60 μ
LINER THICKNESS	70 μ

APPLICATION TEMPERATURE MIN -20°C MAX 90°C

Stored in original packing at a temperature of 21 ° C and 50% relative humidity, the product has a shelf life of 12 months. Before application, thoroughly clean the surfaces to be any dust, oils and fats. The above data cannot be considered a contract or specification. Data represents mean values from tests carried out on samples taken from production. The information may be changed without notice - please ask for the cards to get the latest update. Because of the many operating conditions, we recommend that the user verify the suitability of the product for each application, assuming the responsibilities arising from improper use. Our technicians are at your disposal for any clarification / advice.

REV 2 – 05/06/2025